



SUPER LINER SPECIFICATIONS

POWER	13 HP (9.75 kw) Briggs & Stratton OHV Intek Engine, oil filter with pressure lubrication, anti vibration system, cast iron sleeve, dual element air cleaner
CONFIGURATION	4 Wheel configuration 7" (17 cm) ground clearance
DRIVE	Direct engine mounting to hydrostatic transaxle; Eaton 851 transaxle
SPEED	0 – 7 mph (0 – 11kph)
BRAKING	Dynamic braking through hydrostatic transaxle with parking brake
MAIN FRAME	Heavy gauge square steel tubing, hydraulically formed. Electrically welded. Rear engine placement
TIRES/WHEELS	(2) 16" x 6.50" x 8" (40cm x 16cm x 20cm) Turf Tires (2) 22" x 11" x 8" (56cm x 28cm x 20cm) Turf Tires
WHEEL BASE	45" (114.3cm) Turning radius 10' (3m)
STEERING	Manual front wheel steering, 15" (38cm) diameter, Automotive type, adjustable tilt steering wheel
CONTROLS	Advanced Quadro Z-Gate hand shifter, foot operated paint control
SEAT	High-back, one piece for operator comfort
ELECTRICAL	12 Volt battery (280cca); 12 Volt electric starter
SOUND LEVEL	82 dbA () under normal operating conditions
DIMENSIONS (Inches/cm)	Length – 74" (188 cm); Width – 44" (111 cm); Height – 46" (116 cm) (Length-Width-Height)
WEIGHT	610 lbs (1342 kg)
LIQUID CAPACITIES	35 Gallon (133 liters) steel compressed air tank
SAFETY & CONFORMANCE	Safety start switch on hand shifter
COMPRESSOR	12 Volt air compressor (air pressure up to 50 lbs (110kg)
SPRAY BOX	Front mounted and side mounted; paint line from 2" (1cm) to 5" (13cm); double spray nozzles
HILL CLIMBING ABILITY	Up to 40°