



## SUPER STAR BUNKER RAKE

<b>MODELS</b>	<b>42-000F</b> <b>Super Star SP 3-WD Series/Parallel Traction Drive</b> <b>42-000E</b> <b>Super Star 3-WD Classic Parallel Traction Drive</b> <b>42-001D</b> <b>Super Star 2-WD</b> <b>42-400A</b> <b>Super Star LE 2-WD</b>
<b>POWER</b>	16hp (12 kW) Vanguard V twin cylinder , air cooled, gasoline Cast iron sleeves, 29.3 cu. In. displacement, electronic ignition Full pressure lubrication with oil filter. Engine mounted air cleaner and remote mounted Donaldson air intake filtration
<b>CONFIGURATION</b>	3-wheel tricycle configuration, rear engine placement
<b>DRIVE</b>	Direct multi v-belt drive (with manual clutch for easy cold weather starting) Hydrostatic variable displacement pump to two hydraulic drive motors on rear wheels (Model 42-001D 2-wheel drive) or to two hydraulic drive motors on rear wheels and one hydraulic motor on front wheel (Model 42-000F). Series-Parallel traction drive to all 3 wheels. Hydraulic oil system cooler with engine driven air flow.
<b>SPEED</b>	0-12 mph (0-20 kph) Both 2-Wheel and 3-Wheel Drive Units
<b>BRAKING</b>	Dynamic braking through the hydrostatic transmission Hand operated, disc type park/emergency brake
<b>CONSTRUCTION</b>	Heavy gauge square steel tubing, hydraulically formed, electrically welded.
<b>TIRES/WHEELS</b>	Purchasers choice of (3) 22 x 11 - 10 knobbed sand tires, -or- (3) 23-10.50 x 22 turf tires
<b>STEERING</b>	Manual front wheel steering, 15" (38 cm) diameter automotive type, adjustable tilt steering wheel
<b>CONTROLS</b>	Foot pedal for forward and rear operation of hydraulic system "Pro-Pedal" system connects engine throttle to hydraulic demand (Engine speed increases as hydraulic system demand increases) "Speed Boss" pre-set speed control system on hydrostatic transmission. Hydraulic engage/disengage levers control rear mounted and center mounted implements.
<b>SEAT</b>	Deluxe padded, vinyl covered seat, 1 piece molded, High back support, adjustable operator position
<b>ELECTRICAL</b>	12 volt battery; 12 volt electric starter, side mounted Ignition switch, operator presence switch in seat.
<b>SOUND LEVEL</b>	87dB(A) under normal operating conditions
<b>DIMENSIONS (Inches/m)</b> (Length-Width-Height)	64 in (1.63m) - 57 in (1.45m) - 47 in (1.19m); Wheelbase: 41 in (1.04m) Ground Clearance 9 in (23 cm) - under cultivator
<b>WEIGHT</b>	950 lbs (451 kg)

<b>LIQUID CAPACITIES</b>	Gasoline (unleaded): 5 gallons (19 liter) in high density polyethylene tank Hydraulic system oil: 5 gallons (19 liter) in high density polyethylene tank
<b>SAFETY &amp; CONFORMANCE</b>	Complies with all applicable ANSI, OSHA, and European Machinery Directive standards
<b>OPTIONS</b>	42-315 Front Light Kit; 42-800 Certified ROPS; 15-622 Weather Canopy; 42-805 Fender Kit
<b>IMPLEMENTS</b>	Many efficient and effective implements for constructing and maintaining sand bunkers and other areas on the golf course. Please see below.

#### Rear Mounted Implements

#### SHIP WT.

<b>13-298Q</b>	Fan Rake for Sand Traps	36
<b>13-319</b>	Fan Rake Add On for 13-438 Rake Assembly	20
<b>13-438Q</b>	Sand Trap Rake Assembly	66
<b>13-684</b>	Brush Attachment for all rakes except 42-130	20
<b>13-740</b>	Brush Attachment for 42-130	20
<b>34-191Q</b>	Box Grader	273
<b>42-130Q</b>	84" (213 cm) Mild Steel Tournament Rake	85
<b>42-132Q</b>	72" (189 cm) Mild Steel Tournament Rake	75
<b>42-392Q</b>	84" (213 cm) Multi Brush Rake	100
<b>42-391Q</b>	72" (189 cm) Multi Brush Rake	90
<b>41-501</b>	Typhoon Pumping System	480
<b>43-010</b>	Engine powered Leaf & Debris Blower	180
<b>41-502</b>	EarthWay <sup>®</sup> Spreader	50

#### Center Mounted Implements

<b>42-008</b>	Sand Cultivator	20
<b>42-223</b>	Adjustable Disc Edger	30
<b>42-750</b>	Cart Path/Sidewalk Edger	30
<b>42-340</b>	Sand Cultivator w/Spring Tine Teeth	20
<b>43-130</b>	Weed Cultivator w/ Feet	25

#### Front Mounted Implements

<b>42-011</b>	40" (102 cm) Front Mounted Plow (aluminum blade)	65
<b>43-003</b>	40" (102 cm) Hydraulic Plow	70
<b>42-460</b>	40" (102 cm) Adjustable Angle Plow	85
<b>42-136</b>	60" (155 cm) Front Mounted Manual Plow	75
<b>42-490</b>	60" (155 cm) Adjustable Angle manual Plow	100

#### GREEN STAR

#### ROLLER-BRUSH-SPIKER SYSTEM

<b>42-550Q</b>	<b>Green Star Total RBS System</b> <i>Complete Roller, Brush and Spiker &amp; mounting frame</i>	285
<b>42-586Q</b>	<b>Green Star RBS Main Frame only</b> <i>Mounting frame</i>	50
<b>42-581</b>	<b>Green Star Roller Set (3) only</b> (Requires 42-586Q Main Frame Assembly)	85
<b>42-585</b>	<b>Green Star Brush Set (3) only</b> (Requires 42-586Q Main Frame Assembly)	20
<b>42-582</b>	<b>Green Star Spiker Set (3) only</b> (Requires 42-586Q Main Frame Assembly)	130