



Super Truck Turf Care Vehicle TCV 5000

POWER	35.5hp (26.6 kW) 35.5 HP (26.6 kW) Kubota 1505 four-cylinder diesel engine Liquid Cooled, 12 volt, full pressure lubrication with oil filter.
CONFIGURATION	4-wheel configuration.
DRIVE	Hydrostatic variable speed pump Hydraulic power to two rear wheel drive motors. Planetary rear drive
SPEED	Infinitely variable from 0-10 mph (0- 16 kph)
BRAKING	Dynamic breaking through the hydrostatic transmission Auto spring applied, pressure release parking brake
BATTERY	Automotive type 24F, 12 volt, 900 CCA minimum
LIGHTS	Equipped with pair of headlights. Rocker switch operated
CONSTRUCTION	Heavy gauge square steel tubing, hydraulically formed, electrically welded.
TIRES/WHEELS	Front: (2) 20-10-10 Turf Rear: (2) 29-14-15 Multi-Trac
STEERING	Hydraulic power steering with orbital motor. Automotive 15" steering wheel with tilt adjustment 18' (5.5m) outside turning circle
INSTRUMENTATION	Hour meter, Speedometer, Oil Light, Water Temperature Light, Glo-plug Light
PRIME MOVER CONTROLS	Pedal Hydraulic Actuation, Hand operated throttle control
SEAT	Deluxe seat, padded, vinyl covered 1 piece molded, back support. Adjustable operator position.
ELECTRICAL	12 volt battery, 40 AMPS, operator presence switch in seat.
SOUND LEVEL	98.4dB(A) under normal operating conditions (operators position)
DIMENSIONS (Inches/cm)	128 in (325cm) - 72in (183cm) - 84in (213cm);
Smithco Inc	www.smithco.com 05-25-10

(Length-Width-Height)

Wheelbase: 68in (173cm)

WEIGHT

2355 lbs (1068 kg)

Maximum Payload: 5000 lbs (2268 kg)

LIQUID CAPACITIES

Hydraulic Fluid: 10 gallon (37.8 l) in high density steel tank

Fuel Capacity: 7 Gallon (26.5 l.) in high density polyethylene tank

SAFETY & CONFORMANCE

Smithco engineered 2 post operator protection structure with seat belts standard

Options & Accessories

31-015

Gondola Dump Box

31-028

Cargo Tailgate Box