



## Super Truck Turf Care Vehicle TCV 5000

---

|  |  |
|--|--|
| <b>POWER</b>   | 35.5hp (26.6 kW) 35.5 HP (26.6 kW) Kubota 1505 four-cylinder diesel engine<br>Liquid Cooled, 12 volt, full pressure lubrication with oil filter. |
| <b>CONFIGURATION</b>                                   | 4-wheel configuration.   |
| <b>DRIVE</b>   | Hydrostatic variable speed pump<br>Hydraulic power to two rear wheel drive motors. Planetary rear drive  |
| <b>SPEED</b>   | Infinitely variable from 0-10 mph (0- 16 kph)  |
| <b>BRAKING</b>   | Dynamic breaking through the hydrostatic transmission<br>Auto spring applied, pressure release parking brake                                     |
| <b>BATTERY</b>   | Automotive type 24F, 12 volt, 900 CCA minimum  |
| <b>LIGHTS</b>  | Equipped with pair of headlights. Rocker switch operated   |
| <b>CONSTRUCTION</b>                                    | Heavy gauge square steel tubing, hydraulically formed,<br>electrically welded.   |
| <b>TIRES/WHEELS</b>                                    | Front: (2) 20-10-10 Turf<br>Rear: (2) 29-14-15 Multi-Trac  |
| <b>STEERING</b>  | Hydraulic power steering with orbital motor. Automotive 15" steering wheel with<br>tilt adjustment 18' (5.5m) outside turning circle             |
| <b>INSTRUMENTATION</b>                                 | Hour meter, Speedometer, Oil Light, Water Temperature Light, Glo-plug Light  |
| <b>PRIME MOVER CONTROLS</b>                            | Pedal Hydraulic Actuation, Hand operated throttle control  |
| <b>SEAT</b>  | 2 Deluxe seat, padded, vinyl covered 1 piece molded, back support.<br>Adjustable operator position.  |
| <b>ELECTRICAL</b>                                      | 12 volt battery, 40 AMPS, operator presence switch in seat.  |
| <b>SOUND LEVEL</b>                                     | 88.4dB(A) under normal operating conditions (operators position)   |
| <b>DIMENSIONS (Inches/cm)</b><br>(Length-Width-Height) | 128 in (325cm) - 72in (183cm) - 84in (213cm);<br>Wheelbase: 68in (173cm)   |
| <b>WEIGHT</b>  | 2355 lbs (1068 kg)<br>Maximum Payload: 5000 lbs (2268 kg)  |
| <b>LIQUID CAPACITIES</b>                               | Hydraulic Fluid: 10 gallon (37.8 l) in high density steel tank<br>Fuel Capacity: 7 Gallon (26.5 l.) in high density polyethylene tank            |

**SAFETY & CONFORMANCE**

Smithco engineered 2 post operator protection structure with seat belts standard

**Options & Accessories**

---

|        |                    |
|--------|--------------------|
| 31-015 | Gondola Dump Box   |
| 31-028 | Cargo Tailgate Box |